ENGINE SERVICE TOOLS

OFM TOOLS

OEM TOOLS



OEM TOOLS

Freeze Plug Kit

Master Freeze Plug Tool Kit



Designed to Remove and Install Freeze Plugs Used in Liquid-Cooled Gas and Diesel Engines

Torque Adapter /

24208

Torque Adaptor, Diesel Head Bolt, Ford 6.0L Power Stroke® Engines SKU **298191 999**

• Prevents Damage to the Rear Heat Shield

- Use with OEM 27309 3/4" Drive Torque Wrench and OEM 22398 18 mm Socket • Eliminates the Need to Remove the Evaporator Housing, Saving Time A/C Recharging
- Eliminates the Need to Remove the Truck/Van Cab to Access the Rear Head Bolts

Stretch Belt Mate Kit SKU **544729**

Belt Tools

• Easily Installs All Stretch Fit Belts



Scan for Instructions on How to Use **Stretch Belt**



STORE STOCK

M TOOLS

Serpentine Belt Tool SKU **013620**

- Provides Leverage and Clearance to Release the Spring Pressure and Remove the Tensioner Pullev
- Includes 4 Shallow Sockets, Sizes: 13, 15, 16 and 18 mm; and 1/2" and 3/8" Square Drive Adapters



- Keeps Belt from Falling Off of a Pulley During Belt Installation
- Universal Design to Fit Most Pulley Styles and Sizes
- Super Strong Magnet to Hold the Belt Firmly on the Pulley



Stretch Belt Installation Tool

SKU **227301** 24363

STORE STOCK


- Works on Both Large and Small Pullevs
- Clamping Jaw Allows User to Position Serpentine Belt without the Belt Slipping Out of the Tool

Stretch Belt Remover and Installer SKU 255866 **7799**

LIS59370

33627115

• Compact, One-Piece Tool Can Be Used on the Front or Back Side of the Pulley





OEM TOOLS

Block Testers

and Remove Tensioner Pulley

and Clearance to Release Spring Pressure

• Provides Required Leverage

Block Tester SKU **695104**

33627145

- Quickly and Easily
- When Fluid Turns from Blue to Yellow a Combustion Leak is Present



OEM TOOLS

OEM TOOLS

Test Fluid (8 Oz.) SKU **391381** 25739

299 STORE STOCK

Block Tester





Engine Cylinder Hones



STORE STOCK

- Range: 2" to 7" (51 mm to 128 mm)
- Spring Tension Adjusting Nut for Positive Cutting Action
- Supplied with 4" Medium Grit Stones

Replacement **Stone Sets**



SKU **141540** 2541C 2541M

STORE STOCK

STORE STOCK • 3 Medium Grit • 3 Coarse Grit

SKU **532036** SKU **532044** 2541F

> STORE STOCK • 3 Fine Grit



Flex-Hone™ BC 10 mm (.394") 6.4 mm (.250") SKU **343384**

SKU **341249** BRMBC10M18 **19**99

BRMBC64M24



Flex-Hone™ GB

3-1/2" (89 mm) 3-1/4" (83 mm) SKU **341232** SKU **341239** BRMGB31412 BRMGB31212

3-3/4" 4-1/8" (95 mm) (105 mm) SKU **341317**

SKU **341325** BRMGB33412 BRMGB41812

SKU **341332** BRMGB45812

4-5/8"

(118 mm)

CALL FOR ADDITIONAL SIZES

Throttle Depressors

Brake - Accelerator Pedal Depressor SKU **802194** 24232

- Easy to Adjust
- Extends to 24" • Suitable for Many Diagnostic Applications



Throttle Pedal Depressor

SKU **222525**

- LIS48700 Holds Throttle at a Constant RPM
- Length: 40"



Engine Service

Ford Spark Plug Remover Kit, Triton 3V SKU **0873**07 **099** OTC6918

- Unique Design Helps Prevent Breakage by Locking the Plug Porcelain Core to the Plug Hex Allowing it to Turn as One Complete Unit
- Will Also Pull Plug Porcelain Core if Only Plug Hex is Removed
- Detailed Instructions to Maximize Success Rate

Works on:

- Ford 4.6L 3V V8 Engines Used in 2005-2008 Mustang, 2006-2008 Explorer
- Ford 5.4L 3V V8 Engines Used in 2004-2008
- F-Series, 2005-2008 Expedition, 2005-2008 Lincoln Navigator
- Ford 6.8L 3V V10 Engines Used in 2005–2008 F-Series 250-350-450

Fan Clutch Tools

Universal Pulley and Fan Clutch Holder SKU **547013 6999** 27281

- Fits Many Different Fan Clutches, Cam and Crank Pulleys with Slots or Holes
- Pin Sizes: 6 10 mm, 8 11 mm, 10 12 mm, 11 16 mm • Adjustable Diameter: 1-1/2" - 8-5/8"

Universal Fan Wrench Set SKU 080554 7399

LIS43600

• Use on the Most Popular Applications

• Hooked Wrench Design Holds 2 Nuts or Bolts, Allowing the Technician to Tighten/Loosen the Other 2

• Double-Sided Spanner Style Holding Wrench Will Hold Pressed on Pulleys on Many GM, Jeep and Dodge Vehicles



DEM TOOLS

Fan Clutch Wrench Set SKU **110280**

• Combines OEM #27108 and OEM #27141 Into a Master Set

- Ideal for Removing Fan Clutches from Water Pumps
- Set Includes: 36, 40, 48, 54, 57, 68, 72, 76 and 83 mm Wrench Sizes



Pneumatic Fan Clutch Wrench Set SKU **291409** 17099

LIS43300

· Quickly Removes and Installs Fan Clutch When Repairing the Water Pump or Fan Clutch

• Set Includes Wrench Sizes: 32, 36, 40 mm; 7/8", 1-7/8" and 2"



Fan Clutch Service Set for Mercedes-Benz and BMW SKU **512958**

27224 • Removes Lock Nuts on Thermo Viscous Fans Found

on Mercedes-Benz, BMW and Many Ford Models Includes: (1) Mercedes-Benz Fan Clutch Wrench - 36mm, 40mm and 65 mm Opening

(1) BMW Fan Clutch Wrench - 32 mm Opening (1) BMW Fan Clutch Holding Wrench - 38 mm and 44.5mm and (1) Mercedes-Benz Fan Clutch Holding Tool



Clutch Tools

Flywheel Turner SKU **505066** LIS23800



Duramax Flywheel Lock SKU **301613** LIS22100

- Locks Flywheel in Place When Removing Harmonic Balancer on 6.6L Duramax with Allison Transmissions
- Saves Time by Locking the Flywheel at the Transmission Instead of Having to Remove the Starter for Water Pump Replacement





Tool & Equipment Quarterly



Ford Cam Phaser Noise Repair Kit 4.6/5.4 3V Adding This Kit to a 4.6/5.4L 3V Car, Truck, or SUV Can Help Ensure That Your Cam Phasers Don't Suffer Premature Failure

This Kit is a True, Long Term Repair for Ford Cam Phaser Noise.

SKU **079897** 24206

- Adding This Kit to a 4.6/5.4L 3V Car, Truck, or SUV Will Help Ensure That Your Cam Phasers Don't Suffer Premature Failure
- Included Timing Chain Wedge Tool Increases Ease of Installation
- Included Simple to Use Vehicle Computer Programmer with OBD-II Cable to Disable Cam Phaser Function
- One Kit Corrects Both Cam Phasers
- Cam Phaser is NOT INCLUDED
- Kit will Program (1) Vehicle (One Kit Cannot Program Multiple Vehicles)

Ford Timing Chain Locking Wedge Tool (4.6/5.4 3V Engines) SKU **012647**

24207

- For 2005-14 5.4L and 4.6L 3V
- OE Type Tool
- Allows for Easy Cam Changes without Removing the Timing Cover

24209 24206 SHOWN

Max Energy Tuning Optimizes Spark and Air/Fuel Ratio from Just Off Idle to Wide-Open Throttle. Maximum Horsepower and Torque Gains are Provided to Work Perfectly with the Cam Phaser Kit.

Ford Cam Phaser Noise Kit 4.6/5.4 3V with Tuning

SKU **597001**

OEM TOOLS

- Includes Performance Tuning Optimized for this Kit to Produce Max Horsepower and Torque
- This Kit Also Includes Tuning Options for Airflow, TPMS, Top Speed Limit, Speed of Calibration, Rev Limiter, Shift Firmness, Shift Point, Cooling Fan On/Off Temp
- Note: Not all Features are Available in All Applications the Year, Make, & Model of the Vehicle Will Determine the Feature Set for That Application.
- Cam Phaser is NOT INCLUDED

Valve Train Tools

Valve Spring Compressor SKU **231210**

STORE STOCK

25220

• Designed for Use on Most Trucks and Cars with Overhead Valves



OEM TOOLS

OEM TOOLS

Push Rod Remover SKU **459100**

LIS48300



Quickly Removes Push Rods to Replace the Intake Gaskets without Removing Rocker Arms

Parallel Lift Spring Compressor

Timing Gear Holder SKU **544797** 24387

- Holds the Timing Gear in Place During Removal and Installation and Prevents it from Moving While the Retaining Bolt is Removed
- · Allows the Cam Gear to Rotate to Alian Valve Timina Marks
- Single Lever Locking Design is Easy-to-Us

⊙≡M TOOLS Valve Spring Compressor for 3-Valve Engines

SKU 814391 6999

• Designed to Compress the Valve Spring Without Removing the Camshaft While Servicing the Cylinder Head in Ford 3-Valve Engines

• For Use with Ford 3-Valve 4.6L and 5.4L Engines

Valve Keeper Remover and **Installer Kit**

SKU **011658** LIS36050



- Magnet in Tool Body Captures Keepers
- Works on Toyota 4 Cylinder and



Makes Valve Component Disassembly and Reassembly Fast and Easy

Ford Valve Spring

Compressor SKU **626111** 24434

Piston Tools

• 1-1/2" Deep, Low-Friction

Compressor

SKU **013641**

Wrinkle Band

• Fits 3" to 5"

STORE STOCK

Pistons

24682

• Applications: 1991-2004 Ford Vehicles with 4.6L, 2V, V8 Engines; 4.6 4V, 5.4 V8 and 6.8 V10

• Works with Engine Removed or Installed, Cylinder Head On or Off • Not for Triton 5.4 3V

Piston Ring

SKU **003509**

25083

Expander Pliers

and Distortion During

• Dipped Rubber Handles

the Installation and

Removal Process

for Improved Grip

• Diameter Range: 3-1/8" (80mm) to 4-5/8" (120mm)

• Eliminates Piston Ring Damage


• Strong But Light Frame - Weighs Only 6 Lbs. • Works with Most Valve-in Head and L-Head Engines as Well as Truck and Tractor Engines

SKU **516515**

OEM TOOLS

27075

- Spring Capacity: 1"- 2"
 - Throat Depth: 10'



Ridge

Reamer



⊙≡M TOOLS

SKU **532325** 25051

• Capacity: 3" to 5" (76 mm to 127 mm) • For Use on

Conventional and Slant-Block Engines



Spark Plug Sockets

3/8" Drive 14mm x 12 pt. **Spark Plug Socket** SKU **814164** 22814

• Designed with a Universal Joint for the Installation

and Removal of Spark Plugs Situated in Tight Spaces

• Durable Chrome Moly Steel Construction • Overall Length: 3.75"

OEM TOOLS 14mm x 12 pt. Spark Plug Socket - 1' Extension SKU **814337 94**99

- Designed with a Universal Joint for the Installation and Removal of Spark Plugs Situated in Tight Spaces
- Durable Chrome Moly Steel Construction
- 12" Extended Reach



Cam/Crankshaft Tools

Ford 2.0L. 2.3L. 2.5L Cam Tool Kit SKU **626108** 24448

• Applications: 2.0L DOHC Engines Found in 1994-2003 Ford and Mercury, 2004-2012 2.5L DOHC, 2.3L DOHC 4V and 2.0L DOHC Engines in Ford, Mercury and Mazda, and 2.0L DOHC Engines in 1993-1994 Ford Probe

Honda Crankshaft OEM TOOLS **Pulley Holding Tool** SKU **217379** 27176

• Holds Crankshaft Dampeners When Tightening/Loosening Crankshaft Bolts on Honda and Acura Engines 1990 to Present



OEM TOOLS

OFM TOOLS **Crank Bolt Socket Set 6 Piece**

SKU **919501**

- Set Includes: 17, 19, 21, 22, 26 and 27mm
- Heavy Duty Impact Grade Socket • Provides Increased Torque to Break Loose
- Stubborn Crank Bolt Sockets
- · Constructed with Durable Chrome Molybdenum



Crank Bolt Socket

- Heavy Duty Impact Grade Socket
- Provides Increased Torque to Break Loose Stubborn Crank Bolt Sockets
- Constructed with Durable Chrome Molybdenum

• 1/2" Drive 17 mm

SKU **912348** 25275

19 mm

SKU **919499** 25274 21 mm

25213

SKU **912343**

26 mm SKU **919500**

25219

22 mm

SKU **919496** 25277

27 mm

SKU **919497**



OEM TOOLS

O=M TOOLS

SKU **222524**

LIS38220

24386

• Adjusts to Fit Different Size

• Holds Cam Sprocket in Place When Removing Cam Bolt



DOHC Cam Lock Holder SKU **291419**

LIS36880 • This Versatile Tool Easily Locks and Holds Both Camshaft Sprockets

Firmly in Place · Preserves the Engine Timing During Belt or Chain Replacement



SKU **383452** 27210 • Covers Most Single, Twin Cam

5 Piece Master Cam

Clamp Kit

and Quad Cam Engines • Locks Camshaft to Hold Valve Timing During Timing Belt Replacement



OEM TOOLS

2 Piece Cam Clamp™ Set SKU **238159**

24360 STORE STOCK

• Specifically Designed to Retain Sprocket Wheels While Maintaining Proper Timing During Belt Service

Simple to Use

Installs in Seconds

• Removes or Inserts Camshaft Bearings in Nearly All Engines

• Set Includes: Driving Shaft, Driving Shaft Extension, Expander Unit, (5) Split Driving Plugs, (2) Driving Collars and Centering Cone





Cam Sprockets

• Works on All Single and Dual Overhead Cam Sprockets with Holes



- Easily Removes and Installs Camshaft and Crankshaft Seals Compact Puller with Unique Extracting
- Hooks Engage Seal for Quick Removal • Interchangeable Sleeves and Mandrels Allow Easy Installation of New Seal
- Suits Seals from 21.5 mm 64 mm • Sleeves and Mandrels Made from High
- Strength Fiber Glass Reinforced Polymer



Scan for Instructions

on How to Use This **Universal Seal Tool Kit**

Camshaft Seal Kit SKU **512952** 27222

Crankshaft and

• Install and Remove Oil Seals Between 27mm






and 58mm in Diameter









• Range: 1.125" to 2.69"